

Technical specifications - *Kem* TRACK 60

Attribute	Value
Overall module area	Up to approx. 63 m ²
Module surface width	Up to approx. 10.400 mm
Module surface height	Up to approx. 6.200 mm
PV rating	8 - 11,34 kWp
Load	Up to approx. 950 kg
Tare weight	From 2.000 kg (depending on the model)
Steel construction	Stable, hot-dip galvanized in accordance with DIN EN 1461
Type of drive	Electric, swivel and linear drive
Azimuth angle	280°
Elevation angle	20° to 90°
Operating voltage	230 V / 50 Hz
Power input, drives	Elevation approx. 130 W / azimuth approx. 120 W
Bearing	Maintenance-free friction bearing
Mast diameter	355,6 mm
Ground clearance	From approx. 500 mm to 3.000 mm
Control	Astronomic / autarkic
Remote monitoring	Yes
Backtracking	Yes
Wind/snow load	For all loads, configurable in accordance with DIN EN 1055
Wind protection position	15 m/s
Foundation	Bolted or concrete foundation
Mast anchoring	With flange/armature ring or set in concrete

*Technische Änderungen vorbehalten

Options

Options to extend the modulars of the tracker and control cabinet:

- Lightning protection collecting rods on the tracker
- Mechanical limit switch azimuth
- Battery UPS, with charge status monitoring
- AC-overvoltage protection
- Wind sensor with heating and wind sensor redundancy
- Boost mode, for faster attain of the protection position by wind alarm

[Back](#)